

Durex® Dur-A-Metallic Pigment

Metallic Pigment for Decorative Resinous Flooring Systems

- Description** Durex® Dur-A-Metallic Pigment are special metallic pigments that are designed to create pearlescent, iridescent and translucent finishes used as part of the Durex® Dur-A-Metallic Decorative Flooring System. Designed to be field-blended with clear, high-quality resins to create a metallic finish.
- Uses** Durex® Dur-A-Metallic Pigment is to be used as part of the Dur-A-Metallic Decorative Flooring System.
- Ideal For**
- Commercial showrooms, retail areas
 - Residential Applications
 - Garages
- Features**
- Easy to apply
 - Workability enhances artistic input
 - Hammer Tone and Blended Effects available by using different techniques
 - Custom Colours Available

TECHNICAL DATA

PHYSICAL PROPERTIES

Colours	Standard Colours
V.O.C.	0 g/L
Light Fastness	5-8 (ASTM D4304) <i>Of colourants only. For UV stability a UV stable resin must be used.</i>
Coverage	180 gm (6 oz unit); 120 - 160 ft ²

- Packaging** Durex® Dur-A-Metallic Pigment is packaged in 180 gm jars. Available in standard colours. This product is available in custom colours at an additional cost.
- Storage Conditions** For improved performance, Durex® Dur-A-Metallic Pigment should be sealed and kept in a dry, vented, waterproof location, stacked off the ground, out of direct sunlight and other detrimental conditions. Store materials in ambient temperatures above 5 degrees C and below 35 degrees C. Precondition temperature prior to use.
- Health & Safety** Use under well ventilated conditions with appropriate NIOSH approved respirator and full protective dust protective clothing when handling the product. Keep product out of reach of children. Read published Material Safety Data Sheet for additional information.
- Warranty** Durabond warrants this product is free of manufacturing defects, and will replace at no charge, provided it has been applied within 12 months of purchase, it has been installed for uses suitable for this product and in accordance with the manufacturer's instructions.
- Technical Services** Technical support is available upon request at info@durabond.com. For the latest version of this data sheet, please visit our website at www.durabond.com, call toll free at 1-877-DURABOND (387-2266) or speak with your Durabond Technical Coatings Ltd. sales representative.

DURabond

Technical Coatings Ltd

HEAD OFFICE
55 Underwriters Road
Scarborough, ON M1R 3B4
T 416.759.4474 F 416.759.4470

MISSISSAUGA
6178 Netherhart Road
Mississauga, ON L5T 1B7
T 905.565.9283 F 905.565.9365

EDMONTON
14345 120th Avenue
Edmonton, AB T5L 2R8
T 780.451.6364 F 780.453.9056

INFO@DURABOND.COM

WWW.DURABOND.COM

1.877.DURABOND (387.2266)