

Durex® Dur-A-Quartz Trowel Aggregate

Multi-Coloured Decorative Broadcast Silica Sand Blend for Dur-A-Quartz Decorative Resinous Flooring Systems

Description	Durex® Dur-A-Quartz Trowel Aggregate is a high purity multi-coloured silica sand blend with sub-angular granules in a special blend designed for use in decorative trowel applied flooring systems and for optimal anti-slip in a resinous flooring resin matrix.
Uses	Durex® Dur-A-Quartz Trowel Aggregate is a coloured silica sand blend used in part with decorative trowel resinous flooring systems (Dur-A-Quartz Trowel) to yield a multi-coloured decorative floor with increased strength, especially where sloping and added thickness in required.
Ideal For	<ul style="list-style-type: none">• Institutional Flooring Applications• Health Care Flooring Applications• Medium to heavy-duty processing areas• High traffic lanes and aisles• Wash-down stations, showers and locker rooms
Features	<ul style="list-style-type: none">• Extremely durable, highly abrasion resistant• Easy to apply• Multi-coloured blend• Available in Single or Blended Colours• Custom Colours Available• High UV Resistant version available

TECHNICAL DATA

PHYSICAL PROPERTIES

Colours	Multi-Coloured Blends
Sieve Size	20-30 Mesh
Hardness	6.5-7 (Moh's Hardness Scale)
Specific Gravity	2.65 (ASTM C128-01e1)

Packaging	Durex® Dur-A-Quartz Trowel Aggregate is packaged in 22.7kg (50 lbs) bags. Available in standard colour blends and solid colours. This product is available in custom colours at an additional cost.
Storage Conditions	For improved performance, Durex® Dur-A-Quartz Trowel Aggregate should be sealed and kept in a dry, vented, waterproof location, stacked off the ground, out of direct sunlight and other detrimental conditions. Store materials in ambient temperatures above 5 degrees C and below 35 degrees C. Precondition temperature prior to use.
Health & Safety	Use under well ventilated conditions with appropriate NIOSH approved respirator and full protective dust protective clothing when handling the product. Keep product out of reach of children. Read published Material Safety Data Sheet for additional information.
Warranty	Durabond warrants this product is free of manufacturing defects, and will replace at no charge, provided it has been applied within 12 months of purchase, it has been installed for uses suitable for this product and in accordance with the manufacturer's instructions.
Technical Services	Technical support is available upon request at info@durabond.com . For the latest version of this data sheet, please visit our website at www.durabond.com , call toll free at 1-877-DURABOND (387-2266) or speak with your Durabond Technical Coatings Ltd. sales representative.

DURabond

Technical Coatings Ltd

HEAD OFFICE
55 Underwriters Road
Scarborough, ON M1R 3B4
T 416.759.4474 F 416.759.4470

MISSISSAUGA
6178 Netherhart Road
Mississauga, ON L5T 1B7
T 905.565.9283 F 905.565.9365

EDMONTON
14345 120th Avenue
Edmonton, AB T5L 2R8
T 780.451.6364 F 780.453.9056

INFO@DURABOND.COM

WWW.DURABOND.COM

1.877.DURABOND (387.2266)