

Durex® Broadcast Sand Aggregate

Broadcast & Anti-Slip Silica Sand Blend for Resinous Flooring Systems

Description	Durex® Anti-Slip Aggregate is a high purity silica sand blend with sub-angular granules in a special blend designed for use in broadcasted flooring systems and for optimal anti-slip in a resinous flooring resin matrix.
Uses	Durex® Broadcast Aggregate is a broadcasted silica sand blend used in part with resinous flooring systems to build up thickness and increase strength in resinous flooring systems as well provide anti-slip function when required.
Ideal For	<ul style="list-style-type: none">• Medium to heavy-duty processing areas, especially for food and beverage industry• High traffic lanes and aisles• Heavy-duty production and assembly floors• Garbage rooms• Wash-down stations, showers and locker rooms• Warehouse floors where protection from mechanical abuse is desired and chemical exposure is not severe• Wet Areas or any floor requiring anti-slip
Features	<ul style="list-style-type: none">• Extremely durable, highly abrasion resistant• Easy to apply• Plain blend in colour

TECHNICAL DATA

PHYSICAL PROPERTIES

Colour	Silica Sand Colour – Plain
Service Temperature Range	Min. 0°C/Max. 50°C/Quick Term 95°C
Available Sieve Sizes	Flint #32 (40-50 Mesh) GS-20 (20-30 Mesh) GS-18 (16-20 Mesh) GS-16 (12-16 Mesh)

Packaging	Durex® Broadcast Aggregate is packaged in 22.7kg (50 lbs) bags. Available in different sieve ranges depending on specified anti-slip required. This product is available in custom colours colours at an additional cost.
Storage Conditions	For improved performance, Durex® Duracrete Trowel System should be sealed and kept in a dry, vented, waterproof location, stacked off the ground, out of direct sunlight and other detrimental conditions. Store liquid materials in ambient temperatures above 10 degrees C and below 35 degrees C. KEEP FROM FREEZING.
Health & Safety	Use under well ventilated conditions with appropriate NIOSH approved respirator and full protective dust protective clothing when handling the product. Keep product out of reach of children. Read published Material Safety Data Sheet for additional information.
Warranty	Durabond warrants this product is free of manufacturing defects, and will replace at no charge, provided it has been applied within 12 months of purchase, it has been installed for uses suitable for this product and in accordance with the manufacturer's instructions.
Technical Services	Technical support is available upon request at info@durabond.com . For the latest version of this data sheet, please visit our website at www.durabond.com , call toll free at 1-877-DURABOND (387-2266) or speak with your Durabond Technical Coatings Ltd. sales representative.

DURabond

Technical Coatings Ltd

HEAD OFFICE
55 Underwriters Road
Scarborough, ON M1R 3B4
T 416.759.4474 F 416.759.4470

MISSISSAUGA
6178 Netherhart Road
Mississauga, ON L5T 1B7
T 905.565.9283 F 905.565.9365

EDMONTON
14345 120th Avenue
Edmonton, AB T5L 2R8
T 780.451.6364 F 780.453.9056

INFO@DURABOND.COM

WWW.DURABOND.COM

1.877.DURABOND (387.2266)

09 67 00

BROADCAST SAND AGGREGATE
Broadcast & Anti-Slip Silica Sand Blend for Resinous Flooring Systems