

Durex® Clear Gesso

Transparent Acrylic Coating

Description	Durex® Clear Gesso is a 100% acrylic formulation, designed to provide a clear transparent film protection for decorative design textures. It can also be used as a binder medium for pearlescent and glitter pigments. It offers excellent light stability and water resistance.
Uses	Durex® Clear Gesso can be applied over many types of synthetic and cementitious textured coatings.
Advantages	<p>Durex® Clear Gesso provides the following features:</p> <ul style="list-style-type: none"> • Water-based non-toxic; easy to handle • Excellent dust-proofing properties • Excellent resistance to mild acid • Very economical compared to solvent-based sealers • Re-coatable (does not promote delamination) • Excellent compatibility with all cementitious surfaces

TECHNICAL DATA

PHYSICAL PROPERTIES	
Solids by Weight	26%
Density	1.02 kgs/lt
Finish	Clear, water white, non-yellowing
Viscosity	13600 cp
Coverage	Approximately 8.0 m ² /litre (85 ft ² /gallon) per coat A test should be applied to establish practical coverage on the actual substrate.
V.O.C.	0.02 grams/L
Dry to Touch	30 to 60 min. @ 21°C
Recoating	2-4 hrs
Full Cure	2 days
Dry Film Thickness	2-5 mils

Packaging	Durex® Clear Gesso is readily available in 4 litre (1gal) jugs and 18.9 litre (5gal) pails.
Storage	Store Durex® Clear Gesso in a dry, vented, waterproof location, stacked off the ground at ambient temperatures above 5°C (41°F). Keep materials dry, protected from rapid temperature changes, dampness, moisture and away from direct sunlight. KEEP FROM FREEZING.
Surface Preparation	All substrates must be dry, solid and sound. It must also be free of weak and powdery surfaces, ice, snow, dew, frost, oil, grease-releasing agents and other deleterious materials that may be detrimental to a positive bond.
Application	Durex® Clear Gesso is supplied ready to use. Before each use, thoroughly stir Durex® Clear Gesso until is fully blended. Discard all frozen materials, materials that have formed solid lumps at the bottom of the container and materials that do not appear to be of a homogeneous viscosity. Consult with Durabond Products Limited for questionable surfaces. Apply Durex® Clear Gesso undiluted directly to the surface with brush, roller or a low-pressure sprayer, ensuring good penetration into the substrate and an even coverage of the product. For porous surfaces apply a minimum of two (2) coats.
Limitations	Do not apply when ambient, surface and material temperatures are less than 5°C (41°F) during application and curing period.
Clean-up	Clean all tools promptly after each use with clean water. Do not allow the sealer to dry on tools.
Health and Safety	For information and advice on the safe handling, storage and disposal of chemical products, refer to the most recent SDS sheet containing physical, environmental, toxic and other safety/materials handling data. For Industrial use only. Keep out of reach of children.

Warranty

Durabond warrants this product is free of manufacturing defects, and will replace at no charge, provided it has been applied within 12 months of purchase, it has been installed for uses suitable for this product and in accordance with the manufacturer's instructions.

Technical Services

Technical support is available upon request at info@durabond.com. For the latest version of this data sheet, please visit our website at www.durabond.com, call toll free at 1-877-DURABOND (387-2266) or speak with your Durabond Products Ltd. sales representative.

DURabond

HEAD OFFICE
55 Underwriters Road
Scarborough, ON M1R 3B4
T 416.759.4474 F 416.759.4470

MISSISSAUGA
6178 Netherhart Road
Mississauga, ON L5T 1B7
T 905.565.9283 F 905.565.9365

EDMONTON
14345 120th Avenue
Edmonton, AB T5L 2R8
T 780.451.6364 F 780.453.9056

INFO@DURABOND.COM

WWW.DURABOND.COM

1.877.DURABOND (387.2266)

V3.01