

Durex® Drywall Primer

Acrylic Water-Based Primer

Description	Durex® Drywall Primer is an interior latex primer formulated for application to drywall surfaces.
Uses	Durex® Drywall Primer is used as a primer for drywall substrates prior to the application of paint.
Features	<ul style="list-style-type: none"> • Breathable; allows water vapour within the wall system to evaporate • Excellent adhesion to substrate • Superior hiding power

TECHNICAL DATA

PHYSICAL PROPERTIES	
Product Type	Water-based latex emulsion
Appearance	White milky dense liquid
Viscosity	1,500-2,000 cps
pH Level	6.0 – 6.5
Toxicity	Non-toxic
Coverage	4.08 – 8.16 m ² /L (200-400 ft ² /gal)
Finish Time	Flat
Curing Time	20-30 minutes @ 21C (depending on porosity of substrate)
Substrate Requirements	Clean, sanded and solid taped drywall

Packaging	Durex® Drywall Primer is packaged in 18.9 L pails. This product is available in clear and multiple standard colours. Custom colour matching can also be attained at an additional cost. Please refer to the <i>Durex® Colour Selection Guide</i> for all available colour options.
Storage Conditions	Store Durex® Drywall Primer in a dry, vented, waterproof location, stacked off the ground, out of direct sunlight and other detrimental conditions. Store liquid materials in ambient temperatures above 5 degrees C and below 35 degrees C. KEEP FROM FREEZING.
Coverage	One pail of Durex® Drywall Primer will cover approximately 186 m ² (2,000 ft ²).
Application	DO NOT SUBSTITUTE NOR COMPENSATE DUREX® DRYWALL PRIMER WITH WATER OR OTHER ADDITIVES. Drywall surfaces must be clean and sound, free of weak and powdery substances, dust, dirt, oil, grease and other deleterious materials detrimental to a positive bond. Please consult Durabond Technical Services for questions regarding surface conditions. Thoroughly stir Durex® Drywall Primer in its own pail before each use. Discard all frozen materials, materials which have formed solid lumps at the bottom of the container and materials which do not appear to be of a homogeneous viscosity. Apply Durex® Drywall Primer evenly by roller or brush. Avoid dripping and applying excess primer in any one pass.
Cleaning	Clean all tools promptly after each use with clean water. Do not allow material to dry on tools. Durex® Cleaning Solution CS-100 is available to aid cleaning of soiled areas where primer has dried.
Limitations	Not recommended for use over substrates other than drywall or when ambient, surface and material temperatures are less than 5 degrees C during application and curing periods. Do not apply over surfaces where oils and other contaminants are present, or over previously treated surfaces without proper preparation. Avoid application of this product under hot sun and/or high humidity conditions. For exterior applications only.
Health and Safety	Use under well-ventilated conditions with appropriate respirator approved for organic vapours and rubber gloves when handling the product. Avoid contact with eyes and prolonged contact with skin. If contact occurs, flush immediately with water and seek medical attention if irritation occurs. Harmful if swallowed. Do not induce vomiting. Drink 1-2 glasses of water or milk. Keep product out of reach of children. Read published Material Safety Data Sheet for additional information.

Warranty

Durabond warrants this product is free of manufacturing defects, and will replace at no charge, provided it has been applied within 12 months of purchase, it has been installed for uses suitable for this product and in accordance with the manufacturer's instructions.

Technical Services

Technical support is available upon request at info@durabond.com. For the latest version of this data sheet, please visit our website at www.durabond.com, call toll free at 1-877-DURABOND (387-2266) or speak with your Durabond Technical Coatings Ltd sales representative.

DURabond

Technical Coatings Ltd

HEAD OFFICE
55 Underwriters Road
Scarborough, ON M1R 3B4
T 416.759.4474 F 416.759.4470

MISSISSAUGA
6178 Netherhart Road
Mississauga, ON L5T 1B7
T 905.565.9283 F 905.565.9365

EDMONTON
14345 120th Avenue
Edmonton, AB T5L 2R8
T 780.451.6364 F 780.453.9056

INFO@DURABOND.COM

WWW.DURABOND.COM

1.877.DURABOND (387.2266)

V2.01