

# Durex® Dur-A-Quartz Broadcast Aggregate

## Multi-Coloured Decorative Broadcast Silica Sand Blend for Dur-A-Quartz Decorative Resinous Flooring Systems

<b>Description</b>	Durex® Dur-A-Quartz Broadcast Aggregate is a high purity multi-coloured silica sand blend with sub-angular granules in a special blend designed for use in decorative broadcasted flooring systems and for optimal anti-slip in a resinous flooring resin matrix.
<b>Uses</b>	Durex® Dur-A-Quartz Broadcast Aggregate is a broadcasted coloured silica sand blend used in part with decorative broadcasted resinous flooring systems (Dur-A-Quartz Broadcast) to yield a multi-coloured decorative floor with increased strength as well provide anti-slip function when required.
<b>Ideal For</b>	<ul style="list-style-type: none"><li>· Institutional Flooring Applications</li><li>· Health Care Flooring Applications</li><li>· Medium to heavy-duty processing areas</li><li>· High traffic lanes and aisles</li><li>· Wash-down stations, showers and locker rooms</li><li>· Wet Areas or any floor requiring anti-slip</li></ul>
<b>Features</b>	<ul style="list-style-type: none"><li>· Extremely durable, highly abrasion resistant</li><li>· Easy to apply</li><li>· Multi-coloured blend</li><li>· Available in Single or Blended Colours</li><li>· Custom Colours Available</li><li>· High UV Resistant version available</li></ul>

### TECHNICAL DATA

#### PHYSICAL PROPERTIES

<b>Colours</b>	Multi-Coloured Blends
<b>Sieve Size</b>	30-50 Mesh
<b>Hardness</b>	6.5-7 (Moh's Hardness Scale)
<b>Specific Gravity</b>	2.65 (ASTM C128-01e1)

**Packaging** Durex® Dur-A-Quartz Broadcast Aggregate is packaged in 22.7kg (50 lbs) bags. Available in standard colour blends and solid colours. This product is available in custom colours at an additional cost.

**Storage Conditions** For improved performance, Durex® Dur-A-Quartz Broadcast Aggregate should be sealed and kept in a dry, vented, waterproof location, stacked off the ground, out of direct sunlight and other detrimental conditions. Store materials in ambient temperatures above 5 degrees C and below 35 degrees C. Precondition temperature prior to use.

**Health & Safety** Use under well ventilated conditions with appropriate NIOSH approved respirator and full protective dust protective clothing when handling the product. Keep product out of reach of children. Read published Material Safety Data Sheet for additional information.

**Warranty** Durabond warrants this product is free of manufacturing defects, and will replace at no charge, provided it has been applied within 12 months of purchase, it has been installed for uses suitable for this product and in accordance with the manufacturer's instructions.

**Technical Services** Technical support is available upon request at [info@durabond.com](mailto:info@durabond.com). For the latest version of this data sheet, please visit our website at [www.durabond.com](http://www.durabond.com), call toll free at 1-877-DURABOND (387-2266) or speak with your Durabond Technical Coatings Ltd. sales representative.

# DURabond

Technical Coatings Ltd

**HEAD OFFICE**  
55 Underwriters Road  
Scarborough, ON M1R 3B4  
T 416.759.4474 F 416.759.4470

**MISSISSAUGA**  
6178 Netherhart Road  
Mississauga, ON L5T 1B7  
T 905.565.9283 F 905.565.9365

**EDMONTON**  
14345 120<sup>th</sup> Avenue  
Edmonton, AB T5L 2R8  
T 780.451.6364 F 780.453.9056

[INFO@DURABOND.COM](mailto:INFO@DURABOND.COM)

[WWW.DURABOND.COM](http://WWW.DURABOND.COM)

1.877.DURABOND (387.2266)