



Protect. Enhance. Outperform.

ARCHITECTURAL FINISHES

ACR Smooth Metallic

MONOCHROMATIC ACCENT FINISH SYSTEM



Durex® ACR Smooth Metallic

Durex® ACR SMOOTH METALLIC is ideal for creating distinctive architectural features on exterior/interior wall surfaces and can be applied on new and existing buildings. It provides a very flat, smooth, non-reflective surface incorporating reveals and control joints, affording the designer the flexibility to replicate the appearance of panelized façades.



COLOUR:
SM-2095KG
West Coast

Printed samples represent actual finish colours as closely as possible. Colour appearance may vary by texture, lighting and method of application. Always request a textured sample before ordering.



Bright accent colors marked with KG require Durex Kolor Gard for enhanced fade resistance and durability. Use of Kolor Gard is mandatory to maintain color vibrancy over time. For application details, product specifications, and pricing, consult your Durabond representative before proceeding.



SM-2100KG ISLAND RESORT



SM-2105KG RUBY RED



SM-2110KG TIDE WATER




SM-2070 LICORICE



SM-2090KG GAZPACHO




SM-2095KG WEST COAST



SM-2025

ALPINE WHITE



SM-2080

SMOKE



SM-2050

LAMB SKIN



SM-2030

SILVER STREAK




SM-2035

SILVER FOX




SM-2055

SOMERSET TOUPE



SM-2120

ST PETER SAGE




SM-2060

CAMEROON GREY



SM-2065

COUNTRYSIDE



SM-2045

WRIGHT STONE



SM-2085

TUSCANY




SM-2125

NEVADA SUN




SM-2130

NUTMEG



SM-2115

TETON RANGE



SM-2135

TUDOR BROWN



SM-2145

COOL STEEL



SM-2040

CHARCOAL GREY



SM-1500

BLACK

System Guide

Ensure proper application of ACR Smooth Metallic

Durex® ACR SMOOTH METALLIC is ideal for creating distinctive architectural features on exterior/interior wall surfaces and can be applied on new and existing buildings. It provides a very flat, smooth, non-reflective surface incorporating reveals and control joints, affording the designer the flexibility to replicate the appearance of panelized façades.

PANELIZED PATTERN DESIGN APPROACH

Durex® ACR systems require to be installed in “panelized pattern” separated by reveals with limited panel size. This is best coordinated at the design stage of the project.

REVEALS ALIGNMENT

Introduce panelized pattern design by laying out the reveal pattern in alignment with other façade features / components such as fenestration etc.

DETAILED LAYOUT OF REVEALS

Form part of the design and specification documents. Do not leave reveal layout up to the installer.

TRAINED SKILLED INSTALLERS

Durex® ACR systems should be installed only by qualified trained installers.

INSTALLATION PROCEDURES

Installation process shall strictly follow the recommended procedures – no exceptions – no substitutions.

MAXIMUM PANEL SIZE

Panel size should be kept to a maximum 3m² (32 ft²) area per panel, with maximum dimension in any one direction of 2.44m (8 ft).

QUALITY CONTROL AT ALL STAGES

Best results are achieved when strict quality control measures are implemented throughout all the phases, starting from design through to complete installation.

COMPONENT	PRODUCT	MIX DESIGN	COVERAGE	APPLICATION TEMPERATURE
Base	ACR systems are compatible with any Durex® EIFS Wall System. Please contact your Durabond Representative for additional support.			
Render Coat	ACR Smooth Coat x2	1 Bag ACR Smooth Coat 5.5 L potable Water	100 ft ² / Bag @ 1/16" thick per coat 9.3 m ² / Bag @ 1.6 mm thick per coat (minimum 2 coats required)	5°C to 40°C
Finish Coat	ACR Pearl x2	Single component, no mixing required. Stir prior to use.	200 ft ² / Gal per coat 4 m ² / Liter per coat (2 coats required, add. coats optional)	5°C to 40°C
Sealer	ACR ProCoat Clear	Single component, no mixing required. Stir prior to use.	300 ft ² / Gal per coat 6.2 m ² / Liter per coat (1 coat optional)	5°C to 40°C

DURAbond 

TORONTO OFFICE

55 Underwriters Road
Toronto, ON M1R 3B4
T (416) 759-4474
F (416) 759-4470

MISSISSAUGA OFFICE

6178 Netherhart Road
Mississauga, ON L5T 1B7
T (905) 565-9283
F (905) 565-9365

WESTERN CANADA OFFICE

14604 124 Ave NW
Edmonton, AB T5L 3B3
T (780) 451-6364
F (780) 453-9056

TOLL FREE

TF 1 877 387-2266
E info@durabond.com

durabond.com