Durex[®] Dur-A-Fast Extreme Traffic Bearing Waterproofing System Rapid Return to Service, High Abrasion Resistant PMMA Based Traffic

Bearing Waterproofing System for Extreme Duty Applications



DURAbond

Ideal For

- Parking Decks & Structures subject to extreme abuse and wear
- Exposed Decks and areas subject to snow removal or equipments that impart extreme wear

When to use

- Rapid Turn Around
- Extreme Performance & Abrasion Resistance

Features

- PMMA Technology
- Seamless Waterproofing System
- Extreme Abrasion Resistance
- Withstands Snow Plow Blades and Service
- Return to Service 1 Hour after Final Coat

Colour Availability

Tinted

DUR-A-FAST PRIMER **DUR-A-FAST** primer **MEMBRANE** membrane

DUR-A-FAST SEALCOAT top coat

DUR-A-FAST WEAR COAT

intermediate coat

COMPONENT	PRODUCT	WFT	COVERAGE	APPLICATION TEMPERATURE
PRIMER	Dur-A-Fast Primer	10 mils	160 ft²/Gal	10°C to 35°C
MEMBRANE	Dur-A-Fast Membrane	80 mils	20 ft²/Gal	10°C to 35°C
INTERMEDIATE COAT	Dur-A-Fast Wearcoat + Broadcast with Aluminum Oxide*	100 mils	16 ft²/Gal	10°C to 35°C
TOP COAT	Dur-A-Fast Sealcoat	20 mils	80 ft²/Gal	10°C to 35°C

* Broadcast aluminum oxide to refusal

