

Decorative Floor Coating Options

Use this chart to choose the necessary components for the performance requirements of your system.

Primer Options



Top Coat Options



PRIMER OPTION	ADVANTAGES / USE
Epotel Moisture Block	<p>Advantage: Moisture Mitigating (Blocking) Primer</p> <p>Use: For Concrete Slabs with high moisture content and freshly poured slabs (over 14 days old).</p> <p>Coverage: 72 ft²/Gal @22 mils 95 ft²/Gal @17 mils</p>
Uraflex Citrus Primer	<p>Advantage: Penetrating Primer that adheres to oil and similar contaminants</p> <p>Use: For oil or grease contaminated floors</p> <p>Coverage: 200 ft²/Gal @6 mils DFT</p>
Epotel Multi-Prime	<p>Advantage: Penetrating Primer. VOC Free</p> <p>Use: For better adhesion onto concrete</p> <p>Coverage: 200 ft²/Gal @8 mils DFT</p>
Epotel 80	<p>Advantage: Solvent Based Penetrating Primer</p> <p>Use: For better adhesion onto concrete</p> <p>Coverage: 250 ft²/Gal @7 mils DFT 400 ft²/Gal @4 mils DFT</p>

TOP COAT OPTION	ADVANTAGES / USE
Acrutel 50	<p>Advantage: Easy to Apply Sheen Control & Abrasion Resistant Topcoat Available in Matte, Satin, Semi-Gloss, and Gloss</p> <p>Use: For Medium Traffic and Foot Traffic Applications and for sheen control on decorative floors</p> <p>Coverage: 300 ft²/Gal @3 mils DFT 2 coats recommended</p>
Durathane 90	<p>Advantage: Extremely durable UV Resistant clear topcoat. High Gloss.</p> <p>Use: For a durable, heavy duty topcoat</p> <p>Coverage: 400 ft²/Gal @3 mils DFT 2 coats recommended</p>
Polyuratel	<p>Advantage: Virtually Odour Free Clear and Pigmented Topcoat. Rapid Curing</p> <p>Use: For durable low odour, quick turn-around and pigmented (coloured) applications</p> <p>Coverage: 320 ft²/Gal @5 mils DFT 2 coats recommended</p>

For more information, visit www.durabond.com or call toll free 1 877 387 2266.