

Durex Quantum Select 5.0

High Thermal Resistance - Drained Moisture-Managed Exterior Insulation and Finish System (Adhered)

Description	Durex® Quantum Select 5.0 is an exterior insulation and finish system consisting of Type IV expanded polystyrene insulation with factory-cut channels, insulation adhesive, glass fibre reinforcing mesh, base coats, and a finish texture coat which can be selected from any one of the available Durex Architectural Coatings.
Uses	Durex® Quantum Select 5.0 is suitable for use over a wide range of structurally sound substrates and is recommended for use in buildings which require moisture-managed cladding and higher insulation values per inch.
Features	<ul style="list-style-type: none"> . R-Value 5.0/inch @ -18°C . CAN/ULC S716 compliant . CCMC listed (13103-R) . Continuous venting at floor lines and horizontal terminations, using pre-manufactured vented boards . Positive drainage (through a network of vertical and horizontal channels) . Continuous air/vapour barrier . Simple interfacing with other pressure equalized claddings . 2-hour fire rating in accordance with ULC W456 . Economical . Aesthetic design flexibility . GDDC Factor 47% (Geometrically Defined Drainage Cavity) . CI factor 0.88 RSI (R 5.0) per inch (Continuous Insulation)

TECHNICAL DATA

SYSTEM COMPONENT	STANDARD/METHOD	RESULTS			
INSULATION:		Thermal Resistance		GDDC Factor	
Durex Quantum Select 5.0 Type IV	CAN/ULC S701	0.88 RSI (R 5.0) per inch		47%	
WATER RESISTIVE BARRIER:					
Air / Vapour Barriers	ASTM E96 – Water Vapour Transmission	Method A	Method B		
Durex Green Guard		11 ng/Pa.s.m ²	48 ng/Pa.s.m ²		
Durex Ectoflex		18 ng/Pa.s.m ²	91 ng/Pa.s.m ²		
Air Barriers	(Refer to product specific Technical Data Sheet for more detailed data)				
Durex Flexcrete		400 ng/Pa.s.m ²	972 ng/Pa.s.m ²		
Durex AirStop		185 ng/Pa.s.m ²	505 ng/Pa.s.m ²		
Durex Dur-A-Mastic 100		248 ng/Pa.s.m ²	645 ng/Pa.s.m ²		
Durex Blue Shield		107 ng/Pa.s.m ²	268 ng/Pa.s.m ²		
INSULATION ADHESIVE:					
Durex Flexcrete	ASTM D1623 Adhesion Properties	1.12 MPa (162 psi)			
Durex Monobase	(Refer to product specific Technical Data Sheet for more detailed data)	1.38 MPa (200 psi)			
Durex VCA 3.0		1.02 MPa (148 psi)			
LAMINA:		Retention Physical		Retention Performance	
Impact Resistance	ASTM E2486 – Impact Resistance				
Durex Fiberglass Mesh		Standard	3 N.m	10 N.m	PASS
(Note: Impact resistance level is directly related to the weight and layers of Fiberglass mesh used in the lamina)	(Refer to Table 1.5.9 of the Quantum 5.0 Specifications for detailed selection chart for guidance on level of impact resistance required)	Intermediate	8 N.m	15 N.m	PASS
		High	13 N.m	20 N.m	PASS
		Ultra High	20 N.m	30 N.m	PASS
		Extreme	25 N.m	40 N.m	PASS
Base Coat					
Durex Uniplast/Acrybond “S”	CAN/ULC S114 Noncombustibility	Rated Noncombustible			
Durex Monobase		Rated Noncombustible			
FINISHES:					
Durex Architectural Coatings	CAN/ULC S716.1 & CCMC Report # 13103-R	Durex Architectural Coatings Meet and exceed all requirements			
Classic Series					
Premium Series					
Artisan Series	(Refer to product specific Technical Data Sheet and CCMC Evaluation Report # 13103-R for more detailed data)				
Kolor Gard Series					
Elastomeric (FX) Series					

PERFORMANCE: (Refer CCMC Evaluation Report # 13103-R for complete detailed performance data)		
Fire Protection	CAN/ULC S101 & CAN/ULC S114 (Compliance to NBC 3.2.3.8(1) (b))	Rated as non-combustible cladding ULC design EW21/ EW22
	CAN/ULC S101 (Fire Resistance rated Assemblies)	1 hr. FR rating ULC design W489 (Load Bearing) 2 hrs. FR rating ULC design W485 (Load Bearing) 2 hrs. FR rating ULC design W456 (Non-Load Bearing)
	CAN/ULC S134 (Compliance to NBC 3.1.5.5)	Intertek listing # DPL-WEIFS 30-01
Wind Load Resistance	ASTM E330 – sustained	-2.5 kPa for 60min. – no visible damage to any of the wall components
	ASTM E330 – cyclic	600 cycles alt. 0 to -2.5kPa – no visible damage to any of the wall components
	ASTM E330 – blow-out	-3.75kPa applied for 10 sec. – no visible damage to any of the wall components - max. pressure 7.12 kPa
Water Tightness	ASTM E331	400 Pa pressure difference for 15 min. – no water penetration through the exterior surface finish
System Compliance	CCMC Technical Guide for EIFS CAN/ULC S716.1 EIFS Materials & System	CCMC Evaluation Report # 13103-R Durex Quantum Select 5.0 is fully compliant with: CAN/ULC S716.1 Materials & System CAN/ULC S716.2 Installation of Components & WRB CAN/ULC S716.3 Design Application

Building Code Conformance:
Durex® Quantum 5.0 complies with the following building code requirements (refer to applicable building code)

Classification	Category 1 CAN/ULC S114 & CAN/ULC S101 CAN/ULC S134	Non-Combustible Lamina Fire Test of Exterior Wall Assemblies
Part 3	Article 3.1.5.5 Article 3.1.5.2 Article 3.2.3.7 & Table 3.2.3.7 Sub-Section 3.2.3.8 (1) (b)	Combustible Cladding on Exterior Walls Allowable Minor Combustible Components >10% Unprotected Openings CAN/ULC S101-15 minutes – Non-Combustible Base Coat
Part 5	Section 5.6.1 Sub-Section 5.6.2.1 Section 5.9.4	Protection from Precipitation Sealing and Drainage Exterior Insulation Finish Systems
Part 9	Clause 9.25.2.2(1)(d) Sub-Section 9.25.5.2 Clause 9.27.1.1(5) Section 9.27.2 Article 9.27.3.1 Sub-Section 9.27.13 Article 9.10.14.5 & Table 9.10.14.5(A) Article 9.10.15.5	Insulation Materials CAN/ULC S701 Position of Low Permeance Membranes General (Cladding, Application) Required Protection from Precipitation Elements of Second Plane of Protection Exterior Insulation Finish Systems >10% Unprotected Openings >0.6 m Limiting Distance

Application	Apply all Durex System Products and components, (WRB, insulation, adhesive, base coat, reinforcing mesh, finish coat, sealants) in strict accordance with Durabond’s printed instructions. See Durabond’s Standard Specifications/Details and Durex Product Data Sheets.
Clean-up	Clean all tools promptly after use with clean water. Do not allow mixes to dry on tools.
Storage	Store all Durex® Products and components in a dry vented, waterproof location, stacked off the ground with ambient temperatures above 5°C (41°F). Keep materials dry, protected from dampness and moisture and away from direct sunlight. KEEP FROM FREEZING.
Health and Safety	For information and advice on the safe handling, storage and disposal of chemical products, refer to the most recent SDS sheet containing physical, environmental, toxic and other safety/materials handling data. For industrial use only. Keep out of reach of children.
Warranty	Durabond Products Limited fully warrants their products when used and applied in strict accordance with the printed instructions on product mixing and product application. In any case Durabond’s responsibility shall not exceed either the refund of the purchase price or the replacement of the purchased product.
Technical Services	Technical support is available upon request at info@durabond.com. For the latest version of this data sheet, please visit our website at www.durabond.com, call toll free at 1-877-DURABOND (387-2266) or speak with your Durabond Technical Coatings Ltd. sales representative.

DURabond

HEAD OFFICE
55 Underwriters Road
Scarborough, ON M1R 3B4
T 416.759.4474 F 416.759.4470

MISSISSAUGA
6178 Netherhart Road
Mississauga, ON L5T 1B7
T 905.565.9283 F 905.565.9365

EDMONTON
14345 120th Avenue
Edmonton, AB T5L 2R8
T 780.451.6364 F 780.453.9056

INFO@DURABOND.COM

WWW.DURABOND.COM

1.877.DURABOND (387.2266)

V2.01