

Durex Quantum Select ICF

Advanced-Drained Moisture-Managed Exterior Insulation and Finish System for ICF (Drained Cladding Insulated Concrete Forms)

Description	Durex® Quantum Select ICF is an exterior insulation and finish system consisting of expanded polystyrene insulation with factory-cut channels, insulation adhesive, glass fibre reinforcing mesh, base coats, and a finish texture coat which can be selected from any one of the available Durex Architectural Coatings. Durex® Quantum Select ICF system is ULC rated as non-combustible cladding, meeting building code requirements for non-combustible construction.
Uses	Durex® Quantum Select ICF is suitable for use over a wide range of structurally sound substrates and is recommended for use in buildings which require moisture-managed cladding.
Features	<ul style="list-style-type: none"> . CAN/ULC S716 compliant . CCMC listed (13103-R) . Continuous venting at floor lines and horizontal terminations, using pre-manufactured vented boards . Positive drainage (through a network of vertical and horizontal channels) . Continuous air/vapour barrier . Simple interfacing with other pressure equalized claddings . 2-hour fire rating in accordance with ULC W456 . Economical . Aesthetic design flexibility . GDDC Factor 47% (Geometrically Defined Drainage Cavity) . CI factor 0.65 RSI (R 3.9) per inch (Continuous Insulation) . CI factor 0.70 RSI (R 4.0) per inch Type II EPS (Continuous Insulation)

TECHNICAL DATA

SYSTEM COMPONENT	STANDARD/METHOD	RESULTS				
INSULATION:		Thermal Resistance		GDDC Factor		
Durex Quantum Select Type I	CAN/ULC S701	0.65 RSI (R 3.9) per inch		47%		
Durex Quantum Select Type II		0.70 RSI (R 4.0) per inch		47%		
WATER RESISTIVE BARRIER:						
Air / Vapour Barriers		ASTM E96 – Water Vapour Transmission	Method A	Method B		
Durex Ectoflex			18 ng/Pa.s.m ²	91 ng/Pa.s.m ²		
Air Barriers						
Durex Flexcrete		(Refer to product specific Technical Data Sheet for more detailed data)	400 ng/Pa.s.m ²	972 ng/Pa.s.m ²		
INSULATION ADHESIVE:						
Durex Flexcrete	ASTM D1623 Adhesion Properties	1.12 MPa (162 psi)				
Durex Monobase	(Refer to product specific Technical Data Sheet for more detailed data)	1.38 MPa (200 psi)				
Durex VCA 3.0		1.02 MPa (148 psi)				
LAMINA:			Retention Physical	Retention Performance		
Impact Resistance		ASTM E2486 – Impact Resistance				
Durex Fiberglass Mesh			Standard	3 N.m	10 N.m	PASS
(Note: Impact resistance level is directly related to the weight and layers of Fiberglass mesh used in the lamina)		(Refer to Table 1.5.9 of the Quantum Select ICF Specifications for detailed selection chart for guidance on level of impact resistance required)	Intermediate	8 N.m	15 N.m	PASS
			High	13 N.m	20 N.m	PASS
			Ultra High	20 N.m	30 N.m	PASS
			Extreme	25 N.m	40 N.m	PASS
Base Coat						
Durex Uniplast/Acrybond “S”	CAN/ULC S114 Noncombustibility	Rated Noncombustible				
Durex Monobase		Rated Noncombustible				
Durex Flexcrete						
FINISHES:						
Durex Architectural Coatings		CAN/ULC S716.1 & CCMC Report # 13103-R	Durex Architectural Coatings			
Classic Series			Meet and exceed all requirements			
Premium Series						
Artisan Series						
Kolor Gard Series		(Refer to product specific Technical Data Sheet and CCMC Evaluation Report # 13103-R for more detailed data)				
Elastomeric (FX) Series						

PERFORMANCE:	<i>(Refer CCMC Evaluation Report # 13103-R for complete detailed performance data)</i>	
Fire Protection	CAN/ULC S101 & CAN/ULC S114 <i>(Compliance to NBC 3.2.3.8(1) (b))</i>	Rated as non-combustible cladding ULC design EW23
	CAN/ULC S134 <i>(Compliance to NBC 3.1.5.5)</i>	Intertek listing # DPL-WEIFS 30-01
Wind Load Resistance	ASTM E330 – sustained	-2.5 kPa for 60min. – no visible damage to any of the wall components
	ASTM E330 – cyclic	600 cycles alt. 0 to -2.5kPa – no visible damage to any of the wall components
	ASTM E330 – blow-out	-3.75kPa applied for 10 sec. – no visible damage to any of the wall components - max. pressure 7.12 kPa
Water Tightness	ASTM E331	400 Pa pressure difference for 15 min. – no water penetration through the exterior surface finish
System Compliance	CCMC Technical Guide for EIFS CAN/ULC S716.1 EIFS Materials & System	CCMC Evaluation Report # 13103-R Durex Quantum Select ICF is fully compliant with: CAN/ULC S716.1 Materials & System CAN/ULC S716.2 Installation of Components & WRB CAN/ULC S716.3 Design Application

Building Code Conformance:
Durex® Quantum Select ICF complies with the following building code requirements (refer to applicable building code)

Classification	Category 2 CAN/ULC S114 & CAN/ULC S101 CAN/ULC S134	Non-Combustible Lamina Fire Test of Exterior Wall Assemblies
Part 3	Article 3.1.5.5 Article 3.1.5.2 Clause 3.2.3.7(2) & Table 3.2.3.7	Combustible Cladding on Exterior Walls Allowable Minor Combustible Components >10% Unprotected Openings
Part 5	Section 5.6.1 Sub-Section 5.6.2.1 Section 5.9.4	Protection from Precipitation Sealing and Drainage Exterior Insulation Finish Systems
Part 9	Clause 9.25.2.2(1)(d) Sub-Section 9.25.5.2 Clause 9.27.1.1(5) Section 9.27.2 Article 9.27.3.1 Sub-Section 9.27.13	Insulation Materials CAN/ULC S701 Position of Low Permeance Membranes General (Cladding, Application) Required Protection from Precipitation Elements of Second Plane of Protection Exterior Insulation Finish Systems

- Application** Apply all Durex System Products and components, (WRB, insulation, adhesive, base coat, reinforcing mesh, finish coat, sealants) in strict accordance with Durabond’s printed instructions. See Durabond’s Standard Specifications/Details and Durex Product Data Sheets.
- Clean-up** Clean all tools promptly after use with clean water. Do not allow mixes to dry on tools.
- Storage** Store all Durex® Products and components in a dry vented, waterproof location, stacked off the ground with ambient temperatures above 5°C (41°F). Keep materials dry, protected from dampness and moisture and away from direct sunlight. KEEP FROM FREEZING.
- Health and Safety** For information and advice on the safe handling, storage and disposal of chemical products, refer to the most recent SDS sheet containing physical, environmental, toxic and other safety/materials handling data. For industrial use only. Keep out of reach of children.
- Warranty** Durabond Products Limited fully warrants their products when used and applied in strict accordance with the printed instructions on product mixing and product application. In any case Durabond’s responsibility shall not exceed either the refund of the purchase price or the replacement of the purchased product.
- Technical Services** Technical support is available upon request at info@durabond.com. For the latest version of this data sheet, please visit our website at www.durabond.com, call toll free at 1-877-DURABOND (387-2266) or speak with your Durabond Technical Coatings Ltd. sales representative.



HEAD OFFICE
55 Underwriters Road
Scarborough, ON M1R 3B4
T 416.759.4474 F 416.759.4470

MISSISSAUGA
6178 Netherhart Road
Mississauga, ON L5T 1B7
T 905.565.9283 F 905.565.9365

EDMONTON
14345 120th Avenue
Edmonton, AB T5L 2R8
T 780.451.6364 F 780.453.9056

INFO@DURABOND.COM

WWW.DURABOND.COM

1.877.DURABOND (387.2266)

V2.01