

Durex Equalite

Noncombustible Pressure Equalized Insulated Finish System (Mineral Fiber)

Description Durex® Equalite is a pressure equalized exterior insulation and finish system. The system, which has been independently tested, consists of a membrane air/vapour barrier, mineral fibre insulation, mechanical fasteners, glass fibre reinforcing mesh, continuous vent boards, non-combustible base coats, and a finish texture coat from any one of the available Durex Architectural Coatings.

Uses Durex® Equalite is suitable for use over a wide range of structurally sound substrates and is recommended for use in buildings which require to be of non-combustible construction and pressure equalized cladding.

- Advantages**
- Totally non-combustible cladding
 - Pressure equalized (drained & vented principle)
 - Continuous venting at floor lines and horizontal terminations
 - Vertical orientation of the fibres in the rigid insulation allows for positive drainage
 - Continuous water resistive barrier (self-sealing)
 - Simple interfacing with other pressure equalized cladding systems
 - Continuous high density thermal barrier
 - Aesthetic design flexibility
 - **CI factor 0.70 RSI (R 4.0) per inch (Continuous Insulation)**

TECHNICAL DATA

SYSTEM COMPONENT	STANDARD/METHOD	RESULTS	
INSULATION: Durex Equalite Mineral Fiber	CAN/ULC S702	Thermal Resistance 0.70 RSI (R 4.0) per inch	GDDC Factor -----
WATER RESISTIVE BARRIER: <i>Air / Vapour Barriers</i> Durex Flexseal	ASTM E96 –Water Vapour Transmission	Method A	Method B 2.9 ng/Pa.s.m ²
<i>Air Barriers</i> Durex Flexseal VP Durex AirStop	(Refer to product specific Technical Data Sheet for more detailed data)	629 ng/Pa.s.m ² 185 ng/Pa.s.m ²	972 ng/Pa.s.m ² 505 ng/Pa.s.m ²
INSULATION ATTACHMENT: -Durex“M” fasteners (masonry) -Durex “W” fasteners (wood) -Durex “S” fasteners (steel) -Durex Equalite Washer NC	ASTM B-117 – salt spray DIN 50012 - SO ₂ exposure FM4470 & DIN 50018 SFW	750 hrs. or better 25+ cycles 30 cycles Pass Encapsulated Noncombustible Metal Plate	
LAMINA: Impact Resistance Durex Fiberglass Mesh (Note: Impact resistance level is directly related to the weight and layers of Fiberglass mesh used in the lamina)	ASTM E2486 – Impact Resistance (Refer to Table 1.5.9 of the Equalite Specifications for detailed selection chart for guidance on level of impact resistance required)	Retention Physical Standard 3 N.m Intermediate 8 N.m High 13 N.m Ultra High 20 N.m Extreme 25 N.m	Retention Performance 10 N.m PASS 15 N.m PASS 20 N.m PASS 30 N.m PASS 40 N.m PASS
Base Coat Durex Uniplast/Acrybond “S” Durex Monobase	CAN/ULC S114 Noncombustibility	Rated Noncombustible Rated Noncombustible	
FINISHES: Durex Architectural Coatings Classic Series Premium Series Artisan Series Kolor Gard Series Elastomeric (FX) Series	CAN/ULC S716.1 & CCMC Report # 13103-R (Refer to product specific Technical Data Sheet and CCMC Evaluation Report # 13103-R for more detailed data)	Durex Architectural Coatings Meet and exceed all requirements	

Noncombustible Pressure Equalized Insulated Finish System (Mineral Fiber)

EQUALITE

07240

PERFORMANCE:*(Refer CCMC Evaluation Report # 13103-R for complete detailed performance data)***Fire Protection**CAN/ULC S101 & CAN/ULC S114
*(Compliance to NBC 3.2.3.8(1) (b))*Rated as non-combustible cladding ULC design EW21/
EW22CAN/ULC S101
*(Fire Resistance rated Assemblies)*2 hr. FR rating ULC design W425 (Non-Load Bearing)
1 hr. FR rating ULC design W489 (Load Bearing)
2 hrs. FR rating ULC design W485 (Load Bearing)
2 hrs. FR rating ULC design W456 (Non-Load Bearing)CAN/ULC S134
(Compliance to NBC 3.1.5.5)

Intertek listing # DPL-WEIFS 30-01

Wind Load Resistance

ASTM E330 – sustained

-2.5 kPa for 60min. – no visible damage to any of the
wall components

ASTM E330 – cyclic

600 cycles alt. 0 to -2.5kPa – no visible damage to any
of the wall components

ASTM E330 – blow-out

-3.75kPa applied for 10 sec. – no visible damage to any
of the wall components - max. pressure 7.12 kPa**Water Tightness**

ASTM E331

400 Pa pressure difference for 15 min. – no water
penetration through the exterior surface finish**System Compliance**CCMC Technical Guide for EIFS
CAN/ULC S716.1 EIFS Materials &
SystemCCMC Evaluation Report # 13103-R
Durex Equalite is fully compliant with:
CAN/ULC S716.1 Materials & System
CAN/ULC S716.2 Installation of Components & WRB
CAN/ULC S716.3 Design Application**Building Code Conformance:**

Durex® Equalite complies with the following building code requirements (refer to applicable building code)

Classification	Category 1 CAN/ULC S114	NON-COMBUSTIBLE SYSTEM Non-Combustible Lamina Non-Combustible Insulation
Part 3	Article 3.1.5.1 Article 3.1.5.2 Clause 3.2.3.7(1)&(2) & Table 3.2.3.7	Non-Combustible System Allowable Minor Combustible Components 0-10% Unprotected Openings
Part 5	Section 5.6.1 Sub-Section 5.6.2.1 Section 5.9.4	Protection from Precipitation Sealing and Drainage Exterior Insulation Finish Systems
Part 9	Clause 9.25.2.2(1)(d) Sub-Section 9.25.5.2 Clause 9.27.1.1(5) Section 9.27.2 Article 9.27.3.1 Sub-Section 9.27.13	Insulation Materials CAN/ULC S701 Position of Low Permeance Membranes General (Cladding, Application) Required Protection from Precipitation Elements of Second Plane of Protection Exterior Insulation Finish Systems

Application

Apply all Durex System Products and components, (WRB, insulation, fasteners, base coat, reinforcing mesh, finish coat, sealants) in strict accordance with Durabond's printed instructions. See Durabond's Standard Specifications/Details and Durex Product Data Sheets.

Clean-up

Clean all tools promptly after use with clean water. Do not allow mixes to dry on tools.

Storage

Store all Durex® Products and components in a dry vented, waterproof location, stacked off the ground with ambient temperatures above 5°C (41°F). Keep materials dry, protected from dampness and moisture and away from direct sunlight. KEEP FROM FREEZING.

Health and Safety

For information and advice on the safe handling, storage and disposal of chemical products, refer to the most recent SDS sheet containing physical, environmental, toxic and other safety/materials handling data. For industrial use only. Keep out of reach of children.

Warranty

Durabond Products Limited fully warrants their products when used and applied in strict accordance with the printed instructions on product mixing and product application. In any case Durabond's responsibility shall not exceed either the refund of the purchase price or the replacement of the purchased product.

Technical Services

Technical support is available upon request at info@durabond.com. For the latest version of this data sheet, please visit our website at www.durabond.com, call toll free at 1-877-DURABOND (387-2266) or speak with your Durabond Products Ltd. sales representative.

DURabond

HEAD OFFICE
55 Underwriters Road
Scarborough, ON M1R 3B4
T 416.759.4474 F 416.759.4470

MISSISSAUGA
6178 Netherhart Road
Mississauga, ON L5T 1B7
T 905.565.9283 F 905.565.9365

EDMONTON
14345 120th Avenue
Edmonton, AB T5L 2R8
T 780.451.6364 F 780.453.9056

INFO@DURABOND.COM

WWW.DURABOND.COM

1.877.DURABOND (387.2266)

V2.01